



NOTES:

- | | |
|-----------------------|--------------------------|
| 1.DISPLAY TYPE: | FSTN |
| 2.VIEWING ANGLE: | 6:00 |
| 3.POLARIZER MODE: | TRANSMISSIVE/NEAGTIVE |
| 4.OPERATING TEMP: | -20°C ~ +70°C |
| 5.STORAGE TEMP: | -30°C ~ +80°C |
| 6.LOGIC VOLTAGE: | VDD=5.0V |
| 7.LCD DRIVER VOLTAGE: | Vop=--- |
| 8.DRIVE METHOD: | 1/128DUTY 1/12BIAS |
| 9.DRIVE IC: | T6963C |
| 10.BACKLIGHT TYPE: | SIDE WHITE LED BACKLIGHT |

1	2	3	4	5	6	7	8	9	10	11	12
FG	VSS	VDD	VO	/WR	/RD	/CE	C/D	NC	/RST	DB0	DB1
13	14	15	16	17	18	19	20	21	22	23	24
DB2	DB3	DB4	DB5	DB6	DB7	FS	RV	VEE	A	K	NC

奥朗科技有限公司
Aoran Industry Co.,Ltd

DRAW NO.	G240128GDNSWSD	DRAWN/ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER:A	SCALE:1/1	
⌀	TOLERANCE UNLESS:±0.2			